



| | Type | S/Section |
|-----------------------------------|------|-----------|
| Megane Clio Kangoo | XAXX | 13 |
| | XBXX | 13 |
| | XC0X | 13 |

13 DIESEL INJECTION

- Engine: **F9Q782 and F9Q744** **Basic manuals:**
- Gearbox: **XXX** **Technical Note 3478A**

Modification of a track allocation on a fault page in the Technical Note.

Page 13-48 in Technical Note 3478A regarding the treatment of fault DF149 contains an error. The last check box mentions carrying out a check between tracks **1** and **2**. It should read between tracks **1** and **3**. The box on page 13-48 should therefore be replaced by the one below.

EXAMPLE:

Check **the resistance values** of the flow controller by measuring between:

Track 1 and **track 3** on the injection pump 7-track connector: from **4.9 Ω to 6.5 Ω at 20°C**.

Track 2 and **track 3** on the injection pump 7-track connector: from **4.9 Ω to 6.5 Ω at 20°C**.

If the resistances of the flow sensor are not within this range of values, replace the sensor / fuel flow actuator unit (see Introduction).

"The repair methods given by the manufacturer in this document are based on the technical specifications current when it was prepared.

The methods may be modified as a result of changes introduced by the manufacturer in the production of the various component units and accessories from which his vehicles are constructed."

All copyrights reserved by Renault.

Copying or translating, in part or in full, of this document or use of the service part reference numbering system is forbidden without the prior written authority of Renault.